

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A fastening arrangement for fastening a switching device or the like to a mounting tray, the fastening arrangement comprising a fastening point (12) formed in the switching device or the like, and a lug (10) to be fastened to the fastening point (12), ~~characterized in that~~ wherein the lug (10) is substantially plate-like and comprises at least one protrusion (24), and the fastening point comprises at least three recesses (16) to receive the protrusion (24) in the lug (10) in such a way that the lug (10) is optionally lockable, when being fastened to the switching device or the like, to different positions defined by the recesses (16), one of the positions being a substantially vertical position, another being a substantially horizontal position, and the rest being positions at an angle between these positions.

2. (Currently Amended) A fastening arrangement according to claim 1, ~~characterized in that~~ wherein the recess (16) defining the position between the horizontal and vertical positions of the lug (10) is positioned to lock the lug (10) to a position directed upwards or downwards.

3. (Currently Amended) A fastening arrangement according to claim 1 ~~or 2, characterized in that~~ wherein the recess (16) defining the position between the horizontal and vertical positions of the lug (10) is positioned to lock the lug (10) to a position directed upwards and downwards at an angle of 45°.

4. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 3~~ claim 1, ~~characterized in that~~ wherein the switching device is a modular switching device in which the recess (16) defining the position between the horizontal and vertical positions of the lug (10) is positioned to lock the lug (10) in a

position where the fastening point of the lug (40) to the mounting tray is in line with the outer edge of a module (4).

5. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 4~~ claim 1, characterized in that wherein the fastening point (42) has at least four recesses (46), whereby the lug (40) is lockable to at least two positions between the vertical and horizontal positions of the lug (40).

6. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 5~~ claim 1, characterized in that wherein the protrusion (24) of the lug (40) is substantially on the same plane as the surface of the lug (40).

7. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 5~~ claim 1, characterized in that wherein the protrusion (24) of the lug (40) protrudes outwards from the surface of the lug (40).

8. (Currently Amended) A fastening arrangement according to ~~anyone of claims 1 to 7~~ claim 1, characterized in that wherein the lug (10) has two or more protrusions (24).

9. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 8~~ claim 1, characterized in that wherein both the lug (40) and the fastening point (42) of the switching device or the like comprise a hole (22) for fastening the lug to the switching device or the like.

10. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 9~~ claim 1, characterized in that wherein the lug (40) further comprises a second hole for fastening the lug (40) and thus also the switching device or the like to the mounting tray.

11. (Currently Amended) A fastening arrangement according to ~~any one of claims 1 to 9~~ claim 1, characterized in that wherein the lug (40) further

comprises a slot (26) for fastening the lug (40) and thus also the switching device or the like to the mounting tray.'

12. (New) A fastening arrangement according to claim 2, wherein the recess defining the position between the horizontal and vertical positions of the lug is positioned to lock the lug to a position directed upwards and downwards at an angle of 45°.

13. (New) A fastening arrangement according to claim 12, wherein the switching device is a modular switching device in which the recess defining the position between the horizontal and vertical positions of the lug is positioned to lock the lug in a position where the fastening point of the lug to the mounting tray is in line with the outer edge of a module.

14. (New) A fastening arrangement according to claim 13, wherein the fastening point has at least four recesses, whereby the lug is lockable to at least two positions between the vertical and horizontal positions of the lug .

15. (New) A fastening arrangement according to claim 14, wherein the protrusion of the lug is substantially on the same plane as the surface of the lug.

16. (New) A fastening arrangement according to claim 15, wherein the protrusion of the lug protrudes outwards from the surface of the lug.

17. (New) A fastening arrangement according to claim 16, wherein the lug has two or more protrusions.

18. (New) A fastening arrangement according to claim 17, wherein both the lug and the fastening point of the switching device or the like comprise a hole for fastening the lug to the switching device or the like.

19. (New) A fastening arrangement according to claim 18, wherein the lug further comprises a second hole for fastening the lug and thus also the switching device or the like to the mounting tray.

20. (New) A fastening arrangement according to claim 19, wherein the lug further comprises a slot for fastening the lug and thus also the switching device or the like to the mounting tray.